




JCC-DN7223D

Outdoor PTZ Speed Dome

Features

- 1/4" Colour SONY super HAD CCD
- 480 TV Lines, 0.03 Lux / 0.005 Lux (DSS on)
- Under 2.0 Lux into monochrome view
- Digital Slow Shutter (DSS) and Image freeze
- Auto iris & ICR zoom module
- 48 Back light compensation zone selectable
- F1.6~3.8, f = 3.8~87.4mm
- 230X zoom (23X optical zoom, 10X digital zoom)
- Built-in heater & blower
- Pan range 0~360°, speed 0.5~260°/S
- Tilt range 0~90°, speed 0.5~120°/S
- 128 Preset positions, 1 Auto cruising tour
- RS-485 multi protocols communication

Dimension:



Specification

Model	JCC-DN7223D
Pick Up Element	1/4" Sony super HAD CCD
Zoom Camera Module	Hitachi Day/Night 23x Color Zoom Camera
Picture Element	NTSC: 768(H) x 494(V) / PAL: 752(H) x 582(V)
Synchronization	Internal / External (V-Lock)
Resolution	Horizontal 480 TV Lines
Min. illumination	0.03 Lux / 0.005 Lux (DSS on) , Under 2.0 Lux into monochrome view
Zoom	230X, 23x Optical, 10x Digital
AGC	Auto (24 dB Max)
ALC	Auto / Fix
AES	Auto / Fix
BLC	On / Off
White Balance	Auto (ATW or AWB)
Focus	Auto / Manual
Position	128 Position (Zoom, Focus)
Remote Control	RS-485
On Screen Display	Zoom, Focus, Iris, AWB, AGC, Position, C Gain, APC Gain
Enhancer	Manual H. Gain & V. Gain
H/V Reverse	Off / On
Mask	Off / On
Picture Effect	Posi. / Nega
Cross Line	Off / On
Freeze	Off / On
Pan Range	0~360°, Speed 0.5~260°/sec
Tilt Range	0~90°, Speed 0.5~120°/sec
Auto Panning	128 Preset Positions (Max)
Auto Cruising	1 Auto Cruising Tours(Max)
Power Source	AV24V / 2A
Operation Environment	-30°C ~ +50°C , 10% ~ 90%